Valutek Light-Weight Polyester



Wiper



Part Number: VTPNWLW

Valutek's lightweight polyester wiper is constructed from lightweight, 100% continuous filament polyester in a double-knit, no-run, interlock pattern with cold knife-cut edges. This wiper is a clean and moderately absorbent wiper with low levels of particulate and extractable counts.

Laundered and packaged in a cleanroom.

All Valutek wipers are tested and manufactured in ISO-compliant facilities under Valutek inspection and strict process control to ensure Valutek quality standards and product specifications.

Features

- 100% continuous filament, double-knit polyester fiber
- · Cold knife cut edge
- Moderate absorbency and abrasion resistance
- Chemical compatible with IPA and other common solvents
- Low levels of particulate and extractable counts
- Light weight material reduces both actual cost and the landfill waste impact
- Available in a variety of sizes to suit most applications

Application

As part of the Valutek Microtek product family, this product is recommended for use in cleanroom Class 100-1,000 (ISO 5-6) critical environments.

It is also commonly used for a wide range of applications, including spill control, general wiping, fab breakdown cleaning, suite construction, cleaning medical devices, burnishing magnetic media surfaces, and wiping surfaces.

Pre-Saturated Option:

This wiper is available with customized saturated chemistries to meet your specific application requirements.

Size and Packaging





Part Number	Size	Packaging
VTPNWLW-99	9" x 9" 23 cm x 23 cm	150 ea/bag, 8 bags/case, 1200 ea/case
VTPNWLW-1212	12" x 12" 30 cm x 30 cm	100 ea/bag, 10 bags/case, 1000 ea/case

- All wipers are packed in double poly bags, vacuum sealed, flat packed in carton boxes and with a carton liner.
- Critical environment compatible.
- All wipers are lot traceable with retention samples held in Quality Control for 36 months from manufacturing.

















www.valutek.com

Valutek Light-Weight Polyester Wiper Part Number: VTPNWLW



VTPNWLW Technical Performance

Attribute		Value	Units	Test Method	
Basis Weight		120 ± 10	g/m²	TAPPI T-410	
Absorbency					
Sorptive Efficiency		2	mL/g		
Sorptive Capacity		310	mL/m ²	IEST-RP.CC004.3, Sec 8.1/Sec 8.2	
Sorptive Rate		<1	second		
Particle Counts					
LPC: ≥0.5 µm		<11	10 ⁶ X particles/m ²	IEST-RP.CC004.3, Sec 6.1.3/Sec 6.2.1	
Non Volatile Residue (N	NVR)				
DI Water Extractant		0.02	g/m ²		
IPA Extractant		0.1	g/m ²	IEST-RP.CC004.3, Sec 7.1.2	
Extractable Counts	(lons)				
Sodium(Na ⁺)	<0.2 ppm	Fluoride(F)	<0.2 ppm		
Potassium(K ⁺)	<0.2 ppm	Nitrite(No ₂ -)	<0.2 ppm	IEST-RP.CC004.3, Sec 7.2.2	
Calcium(Ca ²⁺)	<0.5 ppm	Bromide(Br ⁻)	<0.2 ppm		
Magnesium(Mg ²⁺)	<0.2 ppm	Phosphate(PO ₄ ³⁻)	<0.3 ppm		
Ammonium(NH ₄ ⁺)	<0.3 ppm	Chloride(CI ⁻)	<0.2 ppm		
Nitrate(NO ₃ ⁻)	<0.3 ppm	Sulfate(SO_4^{2-})	<0.2 ppm		

^{*}Note: Technical data listed reflects upper/lower limits. Certificates of Analysis available upon request for actual lot-to-lot test data.

